



# Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa  
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45  
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®  
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

<b>Trade name</b>	
CONTACT SPRAY by DECO COLOR® aerosol line	
<b>Article No</b>	
30 720	
<b>Seller/Manufacturer</b>	
Chemmot Ewa Kumorek spółka komandytowa; Józefa Piłsudskiego 59, 32-050 Skawina, Polska	
<b>Product's description</b>	
Moisture remover from electrical installations. Helps in ignition process. Eliminates oxidized places on contacts, causing uninterrupted electricity stream. Preserves electrical systems in vehicles. Prevents oxidation and sulfidation in pipes, electrical contacts, sockets, connectors, fuses and spark plugs.	
<b>Main features</b>	
Provides uninterrupted electricity stream in sockets Protects against water, salt, and weak acids Anticorrosive properties Penetrating properties Removes oxidized places For indoor and outdoor use CFC free	
<b>Physical and Chemical Properties</b>	
Capacity	400 ml
Colour	clear
Application temperature	10-25°C
VOC content	about 80%
Solids content	about 20%
<b>Usage</b>	
Prepare the surface. Clean carefully, degrease, and be sure places you would like to apply to be dry. Shake container vigorously for around 1 minute. Apply selected places evenly from 30 cm. In case of inaccessibility of some places, please use actuator (pipe/tube). Wait few minutes. Start engine. If any problems, spread to whole ignition system. Wait few minutes. If necessary wipe excess with a soft cloth.	
<b>Technical Data Sheet version 05 from 01/03/2022</b>	